



STS600BATTERY TESTER



Overview

STS600BATTERY TESTER

cod. 804242

Digital tester to check the status of the battery, the starting efficiency (CCA), the starter system and the alternator circuit of the vehicle.

Selectable international standards for cars, which correspond to different starting current ranges used by the battery manufacturer. Handy and small in size, it can operate on 12V batteries (WET, GEL, MF, AGM, PbCa, EFB) both disconnected and connected to the vehicle, making testing operations quick and easy.













The graphic display makes the product intuitive and easy to use.

Printing of reports via PC connection.

Features:

- for WET, GEL, MF, AGM, PbCa, EFB batteries from 8-240 Ah at 12V;
- tests performed: battery status, starting capability (CCA), starter system, vehicle alternator circuit;
- selectable reference standards for cars;
- tests can be performed with the battery disconnected or connected to the vehicle;
- graphic display;
- multilingual: EN, IT, FR, DE, ES, RU, PT, NL;
- printing of reports via PC connection.

Technical data

 CODE	CODE 804242	 CURRENT RANGE 100/1400-IEC A	 CURRENT RANGE 26A17/245H2-JIS A
 CHARGING VOLTAGE 12 V		 CURRENT RANGE 100/1400-DIN A	 OPERATING TEMPERATURE (MIN-MAX) 0 - 40 Å,Å°C
 BATTERY CAPACITY 8-240 Ah		 CURRENT RANGE 100/2000-SAE A	 DIMENSIONS 8,0 x 2,4 x 15,0 cm
 CURRENT RANGE 100/2000-EN A		 CURRENT RANGE 100/2000-CA(MCA)- CCA-BCI A	 WEIGHT 0,26 kg